



“Economy Plow”

Dedicated Three Point Hitch Attachment Model

Model ET-SFP36 Economy Tractor Silt Fence Plow 36”

Please Note: A Hyd. Top Link cylinder is required for proper operation of “The Silt Fence Plow” when attached to the 3 point hitch of a tractor.

Approved for a Minimum of 35 HP FWD tractor with a minimum weight of 3000 lbs and up to 60 HP FWD tractors

Standard Features

- Designed for contractors who need to install silt fence periodically
- Dedicated Cat I and II three point hookup
- Installs silt fence down the center
- Weight 600 lbs.
- Front pivot design allows for easy turning
- 36” fabric chute can install 36” and smaller fabric sizes
- Fabric Chute has stainless steel parts in key wear areas
- ¾” thick mole board knife
- Spring loaded 16” diam. cutting coulter cuts through soil, trash and tree roots
- Grade 5 – 5/8” x 3 ½” shear bolt with hardened bushing
- Tube steel A – frame with 1” x 4” stringers
- Replaceable 2” wide hardened knife point
- Fabric tension Spring with 16” diameter fabric retention plate
- Up to 1000’ rolls of silt fence material can be used
- Can Install silt fence 6” deep to 20” deep
- Retractable storage legs with pads for stability

Model ET-SFP42 Economy Tractor Silt Fence Plow 42”

Same Features as above plus the following:

- 42” Fabric Chute can install 42” and smaller fabric sizes
- Weight 645 lbs
- Fabric Curtain is standard Equipment

Model ET-SFP48 Economy Tractor Silt Fence Plow 48”

Same Features as above plus the following:

- 48” Fabric Chute can install 48” and smaller fabric sizes
- Weight 683 lbs
- Fabric Curtain is standard equipment