

Specifications for Rotary Silt Fence Plow
Push Pull Skid loader Silt Fence Plow
Model PP-SFP

Model	RT-SFP36	RT-SFP42	RT-SFP48
Height: Top Knife Setting Bottom Knife Setting	76" 71"	76" 71"	76" 71"
Width with legs down	60"	60"	60"
Width with legs up	46"	46"	46"
Length	120"	131"	137"
Weight	1125 lbs.	1170 lbs.	1208 lbs.
Shipping weight	1200 lbs	1255 lbs	1283 lbs
Cutting coulter	Spring loaded with 16" hardened fluted blade	Spring loaded with 16" hardened fluted blade	Spring loaded with hardened fluted blade
Rear pivot Turning	90° either side of center	90° either side of center	90° either side of center
Rear pivot	2" x 8" grease able pin with hardened bushings	2" x 8" grease able pin with hardened bushings	2" x 8" grease able pin with hardened bushings
Front rotary pivot pin	2" x 8" grease able pin with hardened bushings	2" x 8" grease able pin with hardened bushings	2" x 8" grease able pin with hardened bushings
Offsetting ability in pull position	29" and 40" either side of center	29" and 40" either side of center	29" and 40" either side of center
Offsetting ability in push position	51" either side of center	51" either side of center	51" either side of center
Main beam size	6" x 4" x 3/8"	6" x 4" x 3/8"	6" x 4" x 3/8"
Forklift slots	Standard equipment	Standard equipment	Standard equipment
Mole board knife	1" thick / two position	1" thick / two position	1" thick / two position
Replaceable knife point	2" wide hardened steel	2" wide hardened steel	2" wide hardened steel
Shear bolt protection	5/8" x 4" grade 8 bolt	5/8" x 4" grade 8 bolt	5/8" x 4" grade 8 bolt
Fabric retention plates	16" diameter	16" diameter	16" diameter

Fabric tension spring	Standard equipment	Standard equipment	Standard equipment
Swing dampening cylinder	Self contained/standard equipment	Self contained/standard equipment	Self contained/standard equipment
Skid loader quick-attach	Universal attachment	Universal attachment	Universal attachment
Fabric chute / stainless steel in key wear areas	Can install 36" and smaller fabric sizes	Can install 42" and smaller fabric sizes	Can install 48" and smaller fabric sizes
Fabric curtain	Optional	Standard	Standard
Digging depth	20" maximum	20" maximum	20" maximum

McCormick Equipment – Chris McCormick 515-669-3427